FRAME & FLOOR	WALLS, WINDOWS, DOORS WALL HGT. 8'	ELECTRICAL SGL PHASE	PLUMBING	ROOF 2x6 TOP RAIL 2x ROOF RAIL CLG HGT. 8'	EXTERIOR	A/C & HEAT
FRAME: 12x46	WALLS: 2"x4" STUDS w/ DOUBLE TOP PLATES	ENT. PANEL: (1) 100 AMP	TYPE: CPVC SUPPLY LINES — STUB THRU FLOOR CONNECT & INSULATE	45 MIL "BLACK" EDPM RUBBER	SHEATHING:	HVAC: (1) W36A2-A10
RE-PROCESSED AXLES: (2+1) BEAM: 10" [1]	PLUMBING WALL: 2"x8" @ 24" PER PLAN	LIGHTS: (7) 4' 2-TUBE w/ LENS	PVC WASTE LINES	TRUSS: #P1062605/06 @ 24" O.C.		60 AMP #6 WIRE
HITCH: STD DET XXX	PLYWOOD SUPPORT: PORCH LIGHTS, T.P. HOLDERS	(ELECTRONIC BALLAST)	WALL HUNG LAV: (1) w/ PLYWOOD SUPPORT	BOX (20-24-20) 137"	FULL WRAP HOUSE WRAP	HEAT: 10 KW
JOISTS: 2"x6" @ 16" o.c.	, GRAB BARS , LAV & CABINET	(2) EXTERIOR W.P. PORCH LIGHT w/ PHOTO CELL	VANITY: N/A			
INSULATION: R-21 KF	COVERING: 1/2" VINYL COVERED GYPSUM THRU OUT		MIRROR: (1) 40" AFF TO BOT.	CEILING: 1/2" SEASPRAY	BOT. TRIM: STEEL	DUCT: FIBERGLASS DUCT
	"HAMPTON GREY"	(2) LIGHTED EXIT SIGN w/ BATTERY BACKUP	COMMODE: (1) HANDICAP	FIBERGLASS DUCT (R-6) BRANCH DUCTED SUPPLY REGISTER INTO R.R.	#883 IVORY	(R-6) FIBERGLASS SUPPLY
DECKING: 23/32" T&G ADVANTECH	EXT. INSUL: R-13 KF INT. INSUL: R-11 IN R.R.				SIDING: HI-RIB STEEL	
	EXT. DOORS:	(1) #680 BROAN COMBO VENT FAN/LIGHT		INSULATION: R-49 KF	#883 IVORY	RETURN AIR: SEE PRINT
COVERING: 1/8" BLOCK TILE	(2) 36"x80" H.D. ALUM w/ 4"x24" V.B./ LEVER HDW/ DRIP CAP			DECKING: 7/16" FR DECK		
#51830 COTTAGE TAN	INT. DOORS: (3) 36"x80" 6-PANEL w/ LEVER HDW		WATER HEATER: (1) 4 GALLON	USE 8d NAILS	TOP TRIM: HI-RIB STEEL	
		GFI (1) 110V GFI RECEPT @ 44" AFF	IN OVERHEAD CABINET IN RESTROOM		MANSARD #883 IVORY	THERMOSTAT: PROGRAMMABLE
	WINDOWS: (6) 24"x60" WHITE VINYL/LOW-E TINT INSUL. 1/1 LOW E w/MINI-BLINDS	(1) 110V EXT. W.P. GFI RECEPT (WHILE IN USE)	GRAB BARS: (1) 36" (1) 42" @ 33" AFF	(1) #680 BROAN COMBO VENT FAN/LIGHT		#TH4110D1007
		(1) 110V DED. W/H RECEPT @ 66" A.F.F.	BLOCK FOR 18" VERTICAL GRAB BAR	ATTIC VENTILATION: SEE PRINT	DECALS: N/A	

[1] OUTRIGGER FRAME w/ CROSSMEMBERS & OUTRIGGERS @ 48" O.C.

BONDING STRAP

STRAPS 16" O.C.

3/4" PLYWOOD BEHIND ALL PLUMBING FIXTURES

DBL EXTERIOR STUDS @ 48" O.C.

▼ (3) PHONE JACKS (NO COVER) w/CONDUIT THRU FLOOR

(1) TOILET PAPER HOLDER

STRAPS 16" O.C.
BRANCH DUCTED SUPPLY INTO R.R.

RETURN AIR OPENING
28 1/2" x 14 1/2"

NOTE: USE DBL. GANG BOX FOR DBL. SWITCHES

