FRAME & FLOOR	WALLS, WINDOWS, DOORS	ELECTRICAL	PLUMBING	ROOF	EXTERIOR	A/C & HEAT
BONDING STRAP FRAME: (3) 12x60's BEAM: 12" [1] (RE-PROCESSED) CENTER MODULE (2+2) AXLES: OUTSIDE MODULES (3+2) EACH	WALL HGT. 8' EXT. WALLS: 2"X6" STUDS w/DOUBLE TOP PLATES STRAPS @ 16" O.C.	ENT. PANEL: (3) 100 AMP	TYPE: CPVC SUPPLY LINES STUB SUPPLY LINES THRU FLOOR CONNECT & INSULATE PVC WASTE STUB-OUTS	STRAPS @ 16" O.C. 45 MIL "BLACK" RUBBER	SHEATHING: FULL WRAP HOUSE WRAP	HVAC: (3) W36A2-A10 60 AMP #6 WIRE
	INT. WALLS: 2"X4" STUDS W/ SGL. TOP PLATES	LIGHTS: (26) 4' 2-TUBE W/ LENS (ELECTRONIC BALLASTS)		TRUSS: #F138,216/17 @ 24" O.C		HEAT: 10 KW
	PLUMBING WALL: 8" @ 24" O.C. PER PLAN.	(2) EXT. W.P. PORCH LIGHT W/ PLYW. SUPPORT & PHOTO-CELL	WALL HUNG LAV: (2) w/ PLYW. SUPPORT	TRANSVERSE (24"-31 1/2"-24")		
HITCH: STD DET XXX	PLYWOOD SUPPORT: PORCH LIGHTS, T.P. HOLDER, GRAB BARS,	(3) LIGHTED EXIT SIGNS W/ BATTERY BACK-UP	MIRROR: (2) 40" A.F.F. TO BOTTOM	RIDGE BEAM: SEE PRINT		DUCT: SUPPLY (R-6) RETURN (STD.)
JOISTS: 2"x8" FLOOR JOISTS @ 16" O.C.	LAVS, COUNTER & O.H. CABS. (3/4" PLYWOOD BEHIND ALL PLUMBING FIXTURES)	(2) #680 BROAN COMBO VENT FAN/LIGHT	COMMODE: (2) HANDICAP			FIBERGLASS DUCT
INSULATION: R-30 KF HIGH DENSITY	COVERING: 1/2" (HAMPTON GREY) VINYL COVERED GYPSUM	(1) W.P. HEAT TAPE RECEPT UNDER FLOOR	SPECIAL: (2) TOILET PAPER HOLDER ● 3'-8" FORMICA TOP ONLY @ 34" AFF w/ S.S. BAR SINK (15"x15") w/ 1 1/2" VTR ● 3'-8" FORMICA O.H. CABINET	CEILING: 1/2" SEASPRAY	BOT. TRIM: STEEL	
DECKING: 23/32" T&G	EXT. INSUL: R-19 KF INT. INSUL: R-11 IN R.R.'s	(1) 120V GFI RECEPT @ 44" AFF GFI		DUCT: FIBERGLASS DUCT SUPPLY (R-6) RETURN (STD.)	SIDING: HI-RIB STEEL	
COVERING: 1/8" BLOCK TILE THRU OUT	EXT. DOORS: (2) 36"X80" H.D. ALUM DOOR W/ 4"x24" VIEW BLOCK	(2) STD 120V RECEPTS @ 44" AFF GROUND FAULT PROTECTED				RETURN AIR: SEE PRINT
COTTAGE TAN #51830	LEVER HDW., & DRIP CAP	WATER HEATER RECEPT @ 66" AFF	FORMICA COLOR: WOODGRAIN FRONT w/ ALMOND TOP	INSULATION: R-38 KF	TOP TRIM: HI RIB STEEL	28 1/2"X14 1/2" R.A. OPENING
NO CUTBACKS SEAMS GET 2 1/2" TILE BAR	INT. DOORS: (10) 36"X80" 6-PANEL W/ LEVER HDW. (2) TELL PRIVACY #LC3526 (8) TELL PASSAGE #LC3575	(1) DUAL HEAD EMERGENCY LIGHTS w/ BATT. BACK UP (84" AFF TO THE BOT)		DECKING: 7/16" FR PANEL (USE 8D NAILS)	MANSARD	
[1] OUTRIGGER FRAME W/ CROSSMEMBERS & OUTRIGGERS @ 48" O.C.	WINDOWS: (8) 24"x60" WHITE VINYL/LOW E TINT INSUL. 1/1 w/MINI-BLINDS	(2) 110V EXT. W.P GROUND FAULT RECEPT (WHILE IN USE) (14) WALL MT. J-BOXES w/STUBOUT THRU FLOOR	WATER HEATER: (1) 4 GAL. IN O.H. CAB. IN R.R. GRAB BARS: (2) 36" (2) 42" (33" AFF TO CENTER) BLOCK ONLY FOR (2) 18" VERTICAL GRAB-BARS	(2) #680 BROAN COMBO VENT FAN/LIGHT ATTIC VENTILATION: SEE PRINT	LINE WINDOWS, DOORS & HVAC OPENINGS w/VYCOR TAPE DECALS: N/A	THERMOSTAT: PROGRAMMABLE #TH411D01007

NOTE: USE DBL. GANG BOX FOR ALL DBL. SWITCHES

ALL STOCK STEEL COLORS ARE #883 IVORY

